

## AQUENCE GL 08 FR 15

Known as Optal A 08 FR 15  
March 2013

### PRODUCT DESCRIPTION

AQUENCE GL 08 FR 15 provides the following product characteristics:

<b>Technology</b>	Synthetic Resin
<b>Product Type</b>	Water based
<b>Application</b>	Labeling

### Application Areas

- Pick up adhesive for labeling applications
- Bonding paper, or paper on aluminium foil

### Product Properties

- High wet tack

### Technical Data

#### AQUENCE GL 08 FR 15:

Viscosity, Brookfield - RVT, 7/20/23,	30,000 to 50,000
pH value	5.5 to 7.5

### DIRECTIONS OF USE

#### Preliminary Statement

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

#### Application

On fully automatic labelling machines working with rotary or straight line feed principle.  
Recommended running temperature: 18 to 25 °C

#### Dilution

AQUENCE GL 08 FR 15 is ready to use and shall not be diluted.  
AQUENCE GL 08 FR 15 can not be blended with other adhesives like starch, dextrin or casein adhesives.

#### Cleaning

Uncured adhesive residues can easily be removed with water.  
Dry adhesive residues can be cleaned with hot water.

### STORAGE

Rotate stock, using oldest material first.  
Protect from freezing.  
Keep container covered when not in use to prevent moisture loss and contamination.  
Do not mix with other adhesives.  
When stored in a dry and cool place in the original unopened containers shelf life is as follows.

#### Shelf life:

Shelf-life (in unopened original packaging), months 6  
Refer to expiry date on original packaging.

Frost-Sensitive Yes  
Recommended Storage Temperature, °C 10 to 30

### Classification:

Please refer to the corresponding **safety data sheets** for details on:

**Hazardous Information**  
**Transport Regulations**  
**Safety Regulations**

## ADDITIONAL INFORMATION

### Disclaimer

#### Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

#### **In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

#### **In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

#### **In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

#### Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

#### Reference 0.0

Henkel AG & Co. KGaA  
40191 Düsseldorf, Germany  
Phone: +49-211-797-0

Henkel Corporation  
Bridgewater, NJ 08807, USA  
Phone: +1-908-685-7000

Henkel (China) Co.Ltd.  
201203 Shanghai, China  
Phone: +86-21-2891-8000